

SPECIFICATION

On page 2, line 3 of the patent application:

A rooftop used in combination with jeep-type vehicles, comprises
~~comprising~~ a substantially rectangular top wall having first, second, third,
and fourth

On page 4, lines 2 and 3 of the patent application:

It is yet another object of the present invention to provide a
removable rooftop that provides protection from weather elements such as
wind, ~~such~~ rain, hail, sleet, and snow.

On page 5, line 7 of the patent application:

Figure 4 is a representation of a front view of the instant invention.

Figure 4a is a cut view of the instant invention taken along the line
4a-4a as seen in figure 4 showing the filler material.

Figure 5 illustrates a bottom view of the instant invention.

On page 6 of the patent application:

window frame of door **106**, forms a seal with wedge **38**. This seal reduces
interior cabin noise for the driver and passengers; provides protection from
weather elements such as wind, ~~such~~ rain, hail, sleet, and snow; and helps
protect the driver and passengers from debris while driving.

On page 7, lines 1-12 of the patent application:

jeep-type vehicle **100**, instant invention **10** is strong, stable and
sturdy, essentially a part of the jeep-type vehicle. Front edge **40** secures
onto ridge **102**, seen in figure 1, and base **32** secures onto base **104** of jeep-

1 type vehicle **100**. In the preferred embodiment, jeep-type vehicle **100** is a
2 "JEEP" model "CJ-7", or WRANGLER" up to the year 1998 of
3 DaimlerChrysler. More specifically, the jeep-type vehicle is a vehicle
4 suitable for traveling over rough terrain having four wheels and exhibiting
5 the characteristics or capable of exhibiting the characteristics of a jeep.
6

7 As seen in figures 3 and 5, instant invention **10** comprises sunroof
8 assembly **23**, which is built into support wall **22** in the preferred
9 embodiment. As part of top wall **20**, support wall **22** is structurally
10 designed with additional layering to allow for the installation of sunroof
11 assembly **23**, without compromising the necessary rigid qualities of a
12 rooftop.
13

14 On page 8, line 11 of the patent application:

15 The plastic materials are strong enough to provide protection from
16 weather elements such as wind, rain, hail, sleet, and snow as an example.
17

18 On page 8, lines 22-26 of the patent application:

19 In between the exterior and interior walls of top wall **20**, support wall
20 **22**, side walls **28**, and legs **30**, instant invention **10** may comprise foam **25**,
21 seen in figure 4a, or other filler material to strengthen instant invention **10**.
22 In the preferred embodiment, the foam or filler material provides
23 protection from UV radiation and reduces interior cabin noise for the
24 driver and passengers.
25
26
27
28

1 On page 13, line 3 of the patent application:

2 A removable rooftop for jeep-type vehicles is provided. The rooftop
3 comprises a top wall. Extending approximately perpendicularly from the
4 top wall are first and second side walls.